



## 2011 Late Model Rules

### Chassis and Body:

Full cage required. Maximum body width 83 inches. Maximum body height is 38 inches at back of car. Care must measure no more than 50 inches from center rear axle to back of body or bumper. Bumper ends must be rounded. No sideboards allowed. 8 inch spoiler allowed. Fuel: alcohol or gas allowed. All Sunset Speedway rules apply to Dirt Car races.

Left and right side window panels must match: bottom must be covered (clear lexan or equivalent) or both must be left open.

Brake bias adjusters are allowed: No other adjustable components are allowed within reach of seated driver.

### Spoiler and Weight Package:

602 and 604 crate #2150 and 10 inch spoiler (optional)

Cast block #2250 and 8 inch spoiler (optional)

Aluminum block #2350 and 8 inch spoiler

### Tires:

Hoosier D55 or Hoosier D55 with HTW stamp. As of June 18th all rear tires need to be Hoosier D55 with HTW stamp.

### The Following Applies to all Classes:

The following actions will result in suspension: use of nitrous oxide, alcohol or drug use, dumping gas, oil or chemicals, going to another pit spot in anger, use of traction device of any kind. NEVER approach the flag stand, you will be listened to after the race. During the race: work on car during yellow must be done in the pits. Minor work and refueling ok on red, with two (2) pit crew per car. All tire changes must be done in pits. Any car overrunning time by .9 seconds will be disqualified.

### All Cars:

Must have muffling device resulting in 95 dba at 100 ft. Super traps to be used only with other muffling device. The loudest car over the limit will be sent to the pits for the night. Must have pick up hook, hoop or chain. Must be self starting with full size battery and must be strapped down. Must have clutches except in automatics. All added weight must be bolted to frame with a minimum of two 1/2 inch bolts. All added weight and drivelines must be painted white, silver, or florescent. Any rub rails must be 1 inch from body. Bumper ends must be inset 2 inches from outside edge of tire and must be smooth. No sharp edges. Must have track approved floorboards. Acceptable appearance of car will be by track approval. Numbers must be 18 inches on top and sides. Number must be in center of side door. Number on roof must be readable on the front stretch from the grandstands. Must have 5 inch numbers on front and rear of car.

### Questions on Rules:

Contact Jerry Schram 360-518-2590